CK-102

Crack Width Gauge





Features

- 1. Automatically show the crack width on the screen.
- Automatically take the crack photos. (real-time image display on the screen)
- Stored photos and all data can be reviewed;
- 4. Probe (camera) comes with lighting fixtures can work in dim light;
- Simple alignment of cracks can be automatically reading, without any set up, easy operation;
- Crack photo as a standard BMP format, directly save to any Udisk/ SD card;
- The camera function could catch all test information in time including crack images, test value and zoom images;
- 8. Host and the probe share one rechargeable lithium battery.
- Reference specification:
 JGJ125-99 "dangerous building appraisal standards.

Brief Introduction

CK-10 series crack width gauge can be widely used in bridges, tunnels, buildings,concrete pavement, metal surface crack width testing.





Photos cracks images

The main technical parameters

The maximum detection range	0-8mm	
Accuracy	better than 0.01mm	
Magnification	40times	
The Operating Temperature	-20 ~ 60 ° C	
Host Interface	standard USB	
The storage	can be stored for more than 3000 photos (SD Card is free to expand);	
Image storage format	BMP format 24 bit color 320×240	
Power supply	lithium battery, standby time: 18 hours	
Size	Host 113x70x16.5mm	
Probe	48x56x58mm	
Weight	host 100 grams, 100 grams of the probe	

Standard Delivery

Main Unit	1
Probe (with 1.5 m cable)	1
Quick charger	1
Blowing balloon	1
Aluminum carrying case	1
Manual and warranty card	
Software	1